


Magstripe Reading

Mag 1



The Mag 1 is an undecoded magstripe reader that can be connected to any standard magstripe decoder.



160 Oak St., Glastonbury, CT 06033 USA
Tel: (860) 659-9660 Fax: (860) 657-3860
email: webmaster@interbar.com
<http://interbar.com>

Mag 1 Specifications

Slot Width

0.050" (1.27 mm)

Head Life

1 Track – 300,000 passes
2 Tracks – 600,000 passes

Weight

7 ounces (198.5 grams)

Material

Black polycarbonate

Temperature

-40° to +85°C

Indicators

2 LEDs (optional)

Dimensions

4.6"L x 2.4"W x 1.4"H
(11.68 cm L x 6.10 cm W x 3.56 cm H)

Power

5VDC standard, approximately 30 mils
12VDC or 24VDC (optional)

Tracks


1 or 2 Tracks

Standard Wiring

3 ft (91.5 cm) cable, flying leads or
connectors depending on interface; or
6-pin rear modular jack

How to Order

Order Mag 1 with a code to indicate options required.



Example

Mag 1-20W6R4 =

Mag 1 with magstripe track 2 only,
no LEDs, weatherproofing, #6 screw
size mounting back cover, rear wire
exit and 15-30VDC voltage.

Options Available

Magstripe

Track 2 only – 2
Tracks 1 and 2 – 1

LEDs

No LEDs – 0
Both LEDs – L
Red LED – R
Green LED – G

Weatherproofing

No Weatherproofing – 0
Weatherproofing – W

Cover

#6 – 6
3mm – M

Wire Exit

Rear Wire Exit – R
Side Wire Exit – S
6-pin rear modular jack – 6

Voltage

5VDC – 5
8-15VDC – 2
15-30VDC – 4